

Note: This data sheet is for informational purposes. It is not a commitment to deliver hardware features or functionality. The development, release and timing of features and functionality described in this document are at the sole discretion of Five9 Network Systems.

FIVE9NS T3200 TOWER SERVER



The Five9NS T3200 is dual socket, quad-core or six-core, tower server. Powered by Intel Xeon 5600 series processors, this versatile system provides I/O slot flexibility that enables seamless integration into a variety of OEM applications.

HIGHLIGHTS:

- Variety of expansion slots
- Tower form factor
- Supports Windows, Linux and Solaris Operating Systems
- Remote system management capabilities ideal for central office and other demanding environments
- Easy to customize and integrate into existing infrastructure
- Easy to scale out as business needs grow

Flexible Tower Server

The Five9NS T3200 was designed with OEM needs in mind. With its rich feature set – including 7 expansion slots, remote management capabilities, and high performance Intel 5600 series processors it's an ideal fit for commercial printing and healthcare environments.

Specialty Services

OEM customers can choose from a host of services that will accelerate the integration process and reduce time to market.

With our in-house Product Lifecycle Management service, Five9NS is uniquely positioned to architect systems for OEM customers. The Five9NS T3200 tower server is customizable and you can brand it as your own. We also provide free engineering support via experts who understand the unique requirements of OEM customers.

The Five9NS Product Lifecycle Management service aims to help you proactively manage your product lifecycle. We'll implement a product lifecycle matched to your needs, providing up to a 5-year product life from the date of contract which can be extended upon request.



Note: This data sheet is for informational purposes. It is not a commitment to deliver hardware features or functionality. The development, release and timing of features and functionality described in this document are at the sole discretion of Five9 Network Systems.

FIVE9NS T3200 TOWER SERVER

FEATURES	PRODUCT
Form Factor	Tower (24.4" x 16.9" x 8.7")
Processors	Intel Xeon X5600 series (4 or 6 cores) Intel Xeon E5600 series (4 cores) Intel Xeon X5500 series (4 cores) Intel Xeon E5500 series (4 cores)
Processor Sockets	Two (FC-LGA 1366)
Front Side Bus or HyperTransport	QPI (Quick Path Interconnect)
Chipset	Intel 5520
Memory	Up to 192GB (using UDIMMs or RDIMMs), 12 DIMM sockets, DDR3-1333 ECC
I/O Slots	4 PCIe G2 x8 slots, full height 1 PCIe x4 slot, full height 1 PCI, 32-bit, 33MHz slot, full height 1 Intel I/O expansion slot
SATA Software RAID	Intel Embedded Server RAID Technology (SW RAID 0/1/10)
Optional SAS/SATA RAID	Intel and LSI Logic Host Bus Adapters
Drive Bays	Eight hot swap 3.5" SATA/SAS bays or Twelve hot-swap 2.5" SATA/SAS bays
Hard Drives	3.5 inch SAS (15K rpm): 300GB, 450GB, 600GB 3.5 inch SAS (10K rpm): 450GB, 600GB 3.5 inch SAS (7.2K rpm): 500GB, 1TB, 2TB, 3TB 3.5 inch SATA (7.2K rpm): 500GB, 1TB, 2TB, 3TB 2.5 inch SAS (15K rpm): 146GB, 300GB 2.5 inch SAS (10K rpm): 300GB, 450GB, 600GB, 900GB 2.5 inch Nearline SAS (7.2K rpm): 500GB, 1TB 2.5 inch Nearline SATA (7.2K rpm): 250GB, 500GB, 1TB
Optical Drive	DVD-Multiwriter
Network Interface	Dual Gigabit Ethernet + optional 3 rd dedicated management port
Serial Ports	1 (DB9) + optional 2 nd port
USB Ports	7 ports (4 rear, 2 front, 1 internal Type A)
Power Supply	Single or Redundant AC
Video	Server Engine LLC Pilot II Controller w/ 8MB memory
Management Hardware	Integrated IPMI 2.0 BMC, Optional Remote Management Module
Management Software	Intel Server Management Software 3.X
Operating Systems	Solaris 10, Linux, Windows